



PERFORMANCE CHARACTERISTICS	
VOLTAGE	2700VRMS*
TEMPERATURE	-269°C TO 200°C (HIGH TEMP IS WITH SOCKETS INSTALLED AND LIMITED TO 1HR. CONSULT SST IF HIGHER TEMP BAKE OUT IS NEEDED)
LEAK RATE	<math><1 \times 10E-10 \text{ ATM-CC/SEC (He)}</math>

* VOLTAGE PERFORMANCE LIMITED BY STANDARD 7/16 COAXIAL PLUG.

WWW.SOLIDSEALING.COM

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: 50 OHM DBL ENDED 7/16 CONNECTOR		
REV.	APP'D	DATE	SCALE 1.25:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	7/19/2016	PART NO. FA30979 REV. A	
A2	OG	04/30/2018	CO7160005-13		ENG APPR.	MH	7/20/2016		SALES DWG NO. FA30979SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.