



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA12839	COPPER	330 AMPS
FA12839-02	MOLYBDENUM	165 AMPS
FA12839-03	NICKEL	98 AMPS
FA12839-04	304 STN STL	21 AMPS

PERFORMANCE SPECIFICATIONS	
VOLTAGE:	8KV DC
CURRENT:	SEE TABLE AT LEFT
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 		TITLE 8KV FEEDTHROUGH			
REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JS	04/05/2012	PART NO. (SEE TABLE) REV. A	WWW.SOLIDSEALING.COM
A2	JF	05/09/2024	FTCL0044-0ST		ENG APPR.	JS	04/05/2012		SALES DWG NO. FA12839SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.