

PART NO.	CONDUCTOR MATERIAL	CURRENT
FA17030	COPPER	16 AMPS
FA17030-02	MOLYBDENUM	8.5 AMPS
FA17030-03	NICKEL	5 AMPS
FA17030-04	304 STN STL	1.1 AMPS

RATINGS	
VOLTAGE	1.5KV DC
CURRENT	SEE TABLE AT LEFT
PRESSURE:	500 PSIG @ 20°C
TEMPERATURE	-269°C TO 450°C

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA17030SL REV. A4

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

EIGHT 1.5KV FEEDTHROUGHS

PART NO. FA17030 REV. A

REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	10/03/2007
A4	JS	05/24/2013	MPDC0016-04		ENG APPR.	MH	10/03/2007

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.