


PART NO.	CONDUCTOR MATERIAL	CURRENT	AIR SIDE PLUG
FA17473	NICKEL	25 AMPS	NO
KT17473	NICKEL	25 AMPS	YES
FA17473-02	MOLYBDENUM	46 AMPS	NO
KT17473-02	MOLYBDENUM	46 AMPS	YES

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE LEFT
VOLTAGE:	700V DC
CURRENT:	SEE TABLE LEFT
PRESSURE:	500 PSIG @ 20°C
TEMPERATURE WITHOUT PLUG:	-269°C TO 450°C
TEMPERATURE WITH PLUG:	-55°C TO 125°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

FOUR PIN CONNECTOR

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	10/16/2007
B1	JS	11/26/2012	MPDP0071-1ST		ENG APPR.	MH	07/10/2008

PART NO. (SEE TABLE) REV. B

SALES DWG NO. FA17473SL REV. B1