



PERFORMANCE SPECIFICATIONS	
VOLTAGE:	3KV DC
CURRENT:	185 AMPS
WORKING PRESSURE:	3300 PSIG @ 20°C
BURST PRESSURE:	10000 PSIG @ 20°C
TEMPERATURE:	-80°C TO 350°C*

*CALL SST TO CONFIRM LOWER TEMPERATURE USE

**AVAILABLE WITH CUSTOM CONDUCTOR LENGTHS, THREADED OR UNTHREADED

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA29136SL REV. A1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

3KV PRESSURE FEEDTHROUGH

PART NO. FA29136 REV. A

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JF	01/24/2018
A1	JF	01/24/2018	FTST0171-11		ENG APPR.	JF	01/24/2018

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.