


PERFORMANCE SPECIFICATIONS	
MAXIMUM TEMPERATURE	400°C; MAX HEAT RATE : 3°C/MIN
INDEX OF REFRACTION	1.487

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE

BOROSILICATE GLASS  
VIEWPORT IN CF4.5



REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	CH	5/6/2024
A1	JF	05/14/2024	VPDP0054-12		ENG APPR.	JF	05/14/2024

PART NO. FA49434 REV. A

WWW.SOLIDSEALING.COM

SALES DWG NO. FA49434SL REV. A1

**DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.**