

RATINGS	
VOLTAGE:	2.5 KV DC
CURRENT:	125 AMPS
PRESSURE:	0 PSIG @ 20°C*
TEMPERATURE WITHOUT PLUG:	-25°C TO 205°C
TEMPERATURE WITH PLUG:	-25°C TO 125°C

*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. KT20690SL REV. A2

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:
 ONE PIN CONNECTOR

REV.	APP'D	DATE	SCALE 4:5	DIMENSIONS IN INCHES [mm]
A2	JS	11/26/2012	FTST0108-12	

DRAWN	JS	6/23/2009
ENG APPR.	MH	07/01/2009

PART NO. KT20690 REV. A