



PART NO.	CONDUCTOR MATERIAL	CURRENT
FA10351	COPPER	27 AMPS
FA10351-02	MOLYBDENUM	13.5 AMPS
FA10351-03	NICKEL	8.2 AMPS
FA10351-04	304 STN STL	1.8 AMPS

RATINGS	
VOLTAGE:	5 KV DC
CURRENT:	SEE TABLE AT LEFT
PRESSURE:	3500 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: 5KV FEEDTHROUGH		WWW.SOLIDSEALING.COM 	
REV.	APP'D	DATE	SCALE 2:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/6/2006	PART NO. (SEE TABLE) REV. A		
A2	JS	11/27/2012	FCCL0007-0ST		ENG APPR.	MH	03/21/2006			SOLID SEALING TECHNOLOGY, INC. SALES DWG NO. FA10351SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.