


PLUGS SOLD SEPARATELY:
 -VACUUM SIDE PEEK PLUG FA13604
 -AIR SIDE PLUG KT14877

RATINGS	
VOLTAGE:	500V DC
CURRENT:	5 AMPS
PRESSURE:	1250 PSIG @ 20°C
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

(2) 15 PIN SUB D CONNECTORS

WWW.SOLIDSEALING.COM



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 4:5	DIMENSIONS IN INCHES [mm]	DRAWN	JS	03/26/2010
A2	JF	05/21/2014	MPCL0090-01		ENG APPR.	JS	03/26/2010

PART NO. FA14341 REV. A

SALES DWG NO. FA14341SL REV. A2

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.