


| PART NO. | CONDUCTOR MATERIAL | CURRENT WITH PLUG | CURRENT WITHOUT PLUG |
|------------|--------------------|-------------------|----------------------|
| FA15888 | COPPER | 30 AMPS | 55 AMPS |
| FA15888-02 | MOLYBDENUM | 28 AMPS | 28 AMPS |
| FA15888-03 | NICKEL | 16.5 AMPS | 16.5 AMPS |
| FA15888-04 | 304 STN STL | 3.6 AMPS | 3.6 AMPS |

| | RATINGS | |
|-------------|-------------------|-------------------|
| | WITH PLUG | WITHOUT PLUG |
| VOLTAGE | 20KV DC | 14KV DC |
| CURRENT | SEE TABLE AT LEFT | SEE TABLE AT LEFT |
| PRESSURE: | 1500 PSIG @ 20°C | 1500 PSIG @ 20°C |
| TEMPERATURE | -25°C TO 125°C | -269°C TO 450°C |

MATES WITH POWERPLUG FP10883 & FP10883-02

WWW.SOLIDSEALING.COM

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.



TITLE:
 FIVE 20KV FEEDTHRUS



| REV. | APP'D | DATE | SCALE 4:5 | DIMENSIONS IN INCHES [mm] |
|------|-------|------------|-------------|---------------------------|
| A3 | JS | 05/24/2013 | FTST0069-01 | |

| DRAWN | MH | 07/08/2008 |
|-----------|----|------------|
| ENG APPR. | MH | 07/08/2008 |

PART NO. FA15888 REV. A

SOLID SEALING TECHNOLOGY, INC.
 SALES DWG NO. FA15888SL REV. A3

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.