

PLUGS SOLD SEPARATELY:
 - AIR SIDE W/SOLDER CONTACTS FP18066
 - AIR SIDE W/CRIMP CONTACTS KT18065

| RATINGS | |
|--------------|----------------|
| VOLTAGE: | 1 KV DC |
| CURRENT: | 5 AMPS |
| PRESSURE: | 0 PSIG @ 20°C* |
| TEMPERATURE: | -25°C TO 205°C |

*FOR INTERNAL PRESSURE 5 TO 100 PSIG AN OVERPRESSURE RING IS REQUIRED.

WWW.SOLIDSEALING.COM




SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA19346SL REV. A2

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE:

6 PIN CONNECTOR

PART NO. FA19346 REV. A

| REV. | APP'D | DATE | SCALE 5:4 | DIMENSIONS IN INCHES [mm] | DRAWN | JS | 8/26/2008 |
|------|-------|------------|---------------|---------------------------|-----------|----|------------|
| A2 | JS | 11/26/2012 | MPCL0232-15SL | | ENG APPR. | MH | 11/19/2008 |

DIMENSIONS ARE FOR REFERENCE ONLY. UNLESS NOTED, NO TOLERANCES ARE IMPLIED. CONSULT SST TO DISCUSS YOUR SPECIFIC REQUIREMENTS.